

FTXP-N9 + RXP-N9



Indoor unit		FTXP		20N9	25N9	35N9	
Dimensions	Unit	HeightxWidthxDepth	mm	286 x770 x225			
Weight	Unit		kg	9.00			
Air filter	Type			Removable / washable			
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m ³ /min	4.4 / 5.6 / 7.5 / 9.6	4.4 / 5.8 / 7.5 / 9.9	4.5 / 6.3 / 8.3 / 11.5
		Heating	Silent operation / Low / Medium / High	m ³ /min	5.0 / 6.6 / 8.6 / 10.6		5.1 / 7.0 / 9.0 / 11.5
Sound power level	Cooling			dB(A)	55		
	Heating			dB(A)	55		
Sound pressure level	Cooling	Silent operation/Low/High		dB(A)	19 / 25 / 39	19 / 26 / 40	20 / 27 / 43
	Heating	Silent operation/Low/High		dB(A)	21 / 28 / 39	21 / 28 / 40	21 / 29 / 40
Control systems	Infrared remote control				ARC480A78		
	Wired remote control				BRC073A1		


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data

Outdoor unit		RXP		20N9	25N9	35N9
Dimensions	Unit	HeightxWidthxDepth	mm	556 x740 x343		
Weight	Unit		kg	24		26
Sound power level	Cooling			dB(A)	-	
Sound pressure level	Cooling	High		dB(A)	46	
	Heating	High		dB(A)	47	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10 ~48	
	Heating	Ambient	Min.~Max.	°CWB	-15 ~18	
Refrigerant	Type				R-32	
	GWP				675.0	
	Charge			kg	0.55 /-	0.70 /-
Piping connections	Liquid	OD		mm	6.4	
	Gas	OD		mm	9.5	
	Piping length	OU - IU	Max.	m	20	
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m	12	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50 /220-240	
Current - 50Hz	Maximum fuse amps (MFA)			A	16	

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data		FTXP + RXP		20N9 + 20N9	25N9 + 25N9	35N9 + 35N9	
Cooling capacity	Nom.			kW	1.3 /2.00 /2.6	1.3 /2.50 /3.0	1.3 /3.50 /4.0
Heating capacity	Nom./Max.			kW	1.30 /2.50 /3.50	1.30 /3.00 /4.00	1.30 /4.00 /4.80
Power input	Cooling		Min./Max.	kW	0.31 /0.530 /0.72	0.31 /0.660 /0.72	0.29 /1.01 /1.30
	Heating		Min.	kW	0.25 /0.520 /0.95	0.25 /0.690 /0.95	0.29 /0.990 /1.29
Space cooling	Energy efficiency class				A++		
	Capacity	Pdesign		kW	2.00	2.50	3.50
	SEER				7.20		
	Annual energy consumption			kWh/a	97	121	170
Space heating (Average climate)	Energy efficiency class				A++		
	Capacity	Pdesign		kW	2.20	2.40	2.80
	SCOP/A				4.65	4.61	4.64
	Annual energy consumption			kWh/a	663	728	845

Daikin Europe N.V. Naamloze Vennootschap - Zandvoordestraat 300 - 8400 Oostende - België - www.daikin.eu - BE 0412 120 336 - RPR Oostende



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

ECPEN24-046

01/2024



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.